

BEGe project

Results from detector operations and outlook



MPI für Kernphysik • Heidelberg
LNGS • Gran Sasso



1. BEGe in LAr test results

2. Constraints on front-end bandwidth

Marik Barnabé Heider • Dušan Budjáš • Stefan Schönert

3. Upcoming characterisation of ^{dep}Ge BEGe detectors





**Matteo Agostini • Enrico Bellotti • Dušan Budjáš • Carla Cattadori •
Alexander Hegai • Stefan Schönert • Michal Tarka • Assunta di Vacri**

1. BEGe in LAr test results

2. Constraints on front-end bandwidth

3. Upcoming characterisation of
^{dep}Ge BEGe detectors



BEGe in LAr: GDL test bench





- 1st stage preamp from HdM (in Ar gas in dewar neck)
- warm 2nd stage
- 30 ns rise time

BEGe in LAr: short term test 12. 2009


- Goals:
 - working in LAr?
 - HV scan
- 1st cooling:
high LC, some visible signals,
but no spectrum
→ cure: 3 × methanol bath
- 2nd cooling:
LC~50 pA
FWHM ~1.8 keV




BEGe in LAr: short term test 12. 2009





BEGe in LAr: long term test 2. 2010



LAr refillings






Fit: $y = a \cdot x + b$
 $a = (-0.5 \pm 2.5) \cdot 10^{-3}$
 $b = 5.14 \pm 0.04$




operating voltage: 4.5 kV


BEGe in LAr: overall system stability



BEGe in LAr: pulse-shape discrimination results



DEP acceptance fixed at 90%




Error bars include systematic uncertainty of PSD calibration

1. BEGe in LAr test results
2. Constraints on front-end bandwidth
3. Upcoming characterisation of ^{dep}Ge BEGe detectors




BEGe PSA constraints on front-end bandwidth

- test of PSD performance in dependence on signal bandwidth
- using recorded experimental pulse-data
- step 1: FE bandwidth restriction simulated by various filter methods



BEGe PSA constraints on FE bandwidth

- step 2: PSD on filtered pulses (DEP acceptance always fixed at 90%)



⇒ possibility for improved PSD rejection with optimised shaping

1. BEGe in LAr test results
2. Constraints on front-end bandwidth
3. **Upcoming characterisation of
^{dep}Ge BEGe detectors**

Characterisation of ^{dep}Ge BEGe detectors

Coordinators: Dušan, Assunta

- Participants from several GERDA institutes
- **Goal:** characterise spectroscopic, charge collection and PSD performance of the new BEGe detectors
- **Work plan:**
 - high-voltage scanning
 - energy resolution measurements
 - dead-layer and active volume determination
 - PSD performance tests
 - stability measurement
- **Place:** LNGS, laboratory at Autorimessa 2 (above ground)
- **First detector arrival:** in the next days

Characterisation of ^{dep}Ge BEGe detectors

➤ Schedule:

under review (permanently...)


week day	W 1 (GERDA meeting)				W 2				W 3 (DPG Bonn)				W 4							
	1.3.	2.3.	3.3.	4.3.	5.3.	8.3.	9.3.	10.3.	11.3.	12.3.	15.3.	16.3.	17.3.	18.3.	19.3.	22.3.	23.3.	24.3.	25.3.	26.3.
task1	equipment and lab preparation				1aMCoArr	1dMCoArr	1eMBa		1fMCo	1dFCoArr	1gFTh		1hF(M)Am_c			1gFCo + Th + background?		1bFAM_c	1cFCs	
task2	MCA system check with LNGS BEGe				FADC check with LNGS BEGe (incl. 228Th PSD)															
Dusan																				
Assunta																				
Matteo																				
Michal																				
Alexander																				
Notes:																				
tasks should include time for measurement analysis																				
code of the task: detector number; measurement code (small letter, see .doc file); DAQ system (FADC or MCA, F or M); source (with _c when collimated)																				
week day	W 5			Easter			W 6			W 7				W 8						
	29.3.	30.3.	31.3.	1.4.	2.4.	5.4.	6.4.	7.4.	8.4.	9.4.	12.4.	13.4.	14.4.	15.4.	16.4.	19.4.	20.4.	21.4.	22.4.	23.4.
task1	----- 1jMCoAm (stability 1 month) -----																			
task2							2aMCoArr			2dMCoArr	2eMBa		2fMCo	2dFCoArr	2gFTh + Co + background				2cFCs	2bFAM_c
Dusan																				
Assunta																				
Matteo																				
Michal	?	?	?																	
Alexander																				
week day	W 9				W 10					W 11									
	28.4.	29.4.	30.4.	1.5.	2.5.	5.5.	6.5.	7.5.	8.5.	9.5.	12.5.	13.5.	14.5.	15.5.	16.5.					
task1	1fFTh_c																			
task2	2hMAM_c ?				----- 2jMCoAm (stability) -----					2iFTh_c										
Dusan																				
Assunta																				
Matteo																				
Michal																				
Alexander																				

Summary and conclusions


- BEGe detector successfully operated in LAr: 1.8 keV FWHM, stable operation, PSD performance same as in vac. cryostat
- PSD requirements on front-end bandwidth not very demanding: ~100 ns risetime sufficient
- Ready for acceptance testing campaign of the new ^{dep}Ge BEGe detectors, characterisation of the 1st detector starting after the meeting

Backup slides

BEGe in LAr: short term test 12. 2009



BEGe in LAr: short term test 12. 2009




Region	LAr/GDL	Vacuum/Hd
DEP	0.90 ± 0.02	0.90 ± 0.02
1621 keV	0.12 ± 0.02	0.11 ± 0.01
SEP	0.07 ± 0.01	0.06 ± 0.01
2614 keV	0.102 ± 0.001	0.095 ± 0.001
$Q_{\beta\beta}$	0.42 ± 0.03	0.42 ± 0.02

BEGe PSA constraints on FE bandwidth

moving-average smoothing

smoothing span [points]:

5, 7, 9, 13, 17 ...




BEGe PSA constraints on FE bandwidth

smoothing via local regression using weighed least squares


smoothing span [points]:

9, 11, 13, 15, 17, 19, 21, 23, ...



BEGe PSA constraints on FE bandwidth

IIR Butterworth filter, 12 dB drop




BEGe PSA constraints on FE bandwidth

IIR Butterworth filter, 24 dB drop

pass-band frequency [MHz]:

8 7 6 5 4 3 2 1



Characterisation of ^{dep}Ge BEGe detectors

Measurements list

Measurement	Source	DAQ
a. high voltage scanning (incl. “bathtub region”)	⁶⁰ Co (+ ²⁴¹ Am) + pulser	MCA
b. high voltage scanning for average PS check	collimated ²⁴¹ Am	FADC
c. high voltage scanning with a single-peak source	¹³⁷ Cs	FADC or MCA
d. energy resolution, peak tails, etc. check (shaping constant scan, predetermined number of events)	⁶⁰ Co (+ ²⁴¹ Am) + pulser	MCA and FADC
e. dead layer determination	¹³³ Ba (or ²⁴¹ Am)	MCA
f. active volume determination	⁶⁰ Co	MCA
g. PS discrimination (PSD) performance tests	²²⁸ Th, ⁶⁰ Co + background	FADC
h. charge collection and dead layer variation; lateral and front surface scan	collimated ²⁴¹ Am + positioning device	MCA and FADC
i. check of PSD sensitivity loss near n+ electrode	collim. ²²⁸ Th, background	FADC
j. long-term performance stability test	⁶⁰ Co (+ ²⁴¹ Am) + pulser	MCA