

# **LAr Scintillation light readout with Silicon Photomultipliers**

Allen Caldwell, Béla Majorovits, Xiang Liu,  
József Janicskó Csathy, \*Hossein Aghaei-Khozani

March 17, 2010

# Outline

- Introduction
- SiPMs, a candidate for LAr scintillation light readout?
- Characterization of SiPM at cryogenic temperatures
- Summary and outlook

# GERmanium Detector Array (GERDA)


Is a double beta decay experiment in the underground laboratory LNGS, Italy

- Enriched germanium is serving as source and detector at the same time.
- Extremely long half life → extremely low background
- Bare HPGe detectors are operated in LN/LAr
- LAr is: 

{	1. cooling liquid
	2. passive shielding
	3. <b>scintillator</b>

Could we use LAr scintillation light to build an active veto in a low background experiment like GERDA?


# GERDA



# Motivation of a LAr veto

The  $0\nu\beta\beta$  ( $2n \rightarrow 2p + 2e$ ) decay is a single site event.

Segmented detectors can identify multi site events as background. However if singly Compton scattered gamma escapes detector no identification as background is possible.





$0\nu\beta\beta$  decay Q-value = 2.039MeV. In principal all  $\gamma$  sources with a higher energy are dangerous.

$^{208}\text{Tl}$  e.g. from the decay chain of natural  $^{232}\text{Th}$  emits  $\gamma$  with an energy of 2.614MeV.

Detecting scintillation light in LAr from Compton scattered gammas could increase background identification efficiency.

# Heidelberg setup

The GERDA group from MPIK in Heidelberg accomplished background suppression via LAr scintillation light read out with PMTs.(2008JINST 3 P08007)



A background suppression of a factor of ten observed by the Heidelberg Group motivated our studies.

# Our goal

PMTs weigh about one kilogram. Their radioactivity is high  
→ Our goal is to replace conventional PMTs by SiPMs


## Silicon Photo Multiplier characteristics:

- Very small devices (mass of some mg). We expect a much lower radioactivity.
- They do work at cryogenic temperatures
- Do not require HV (HV can lead to problems in Ar atmosphere)
- UV sensitive. Peak is at 400nm
- High photon detection efficiency (PDE) of up to 65%
- Relatively cheap


⇒ excellent candidate for active veto in LAr

# So what is a SiPM?

Take a couple of APDs in Geiger mode...




... and arrange them in an array




KAPDC0029EA

This is what a SiPM chip looks like



The number of fired pixels will tell how many photons were detected. Outstanding 1p.e resolution!



# SiPM properties at cryogenic temperature

- Equipment and experimental setup.
- Pulse shape in LN.
- Gain as a function of temperature and bias.
- Dark rate as a function of temperature.


# Hamamatsu's MPPC



We tested three different SiPMs. The following specifications were given by Hamamatsu.


Number of pixels	100	400	1600
Pixel size	$100\mu\text{m} \times 100\mu\text{m}$	$50\mu\text{m} \times 50\mu\text{m}$	$25\mu\text{m} \times 25\mu\text{m}$
PDE at peak value	65%	50%	25%
Dark count at RT	600-1000 kHz	400-800 kHz	300 - 600 kHz
Gain at RT	$2.75 \times 10^6$	$7.5 \times 10^5$	$2.4 \times 10^5$

# Setup




- Bias circuit and preamplifier built on one printed circuit board at room temperature
- SiPM is submerged in LN
- coax. cable between the SiPM and the PCB

- Gas tight dewar filled with LN
- LN evaporates slowly  
→ temperature increases continuously
- PT100 for temperature readout




# Pulse shape in LN

The decay time increases at low temperatures by a factor of 6.





$$\tau = 45\text{ns}$$




$$\tau = 440\text{ns}$$

The quenching resistor is temperature dependent. Slow component from RC-circuit. Sharp peak from parasitic capacitances.



# Gain v. temperature and bias

Does the gain drop with decreasing temperatures?




The gain is not a function of the temperature but strongly depends on  $V_{\text{bias}}$ . We have to reduce the bias at low temperatures to operate at constant gain.

# Breakdown voltage v. temperature

$$V_{\text{bias}} = V_{\text{bd}} + V_{\text{over}}$$

$V_{\text{bd}}$  is the minimum bias required to operate a SiPM in Geiger mode.  
 $\text{Gain}(V_{\text{bd}}) = 0 \rightarrow V_{\text{over}}$  defines the gain.




$$V_{\text{bd}} = V_{\text{bd}}(T)$$

$\rightarrow$  To operate at constant overvoltage we have to reduce the bias.

# Dark rate v. temperature

A nice property of SiPMs is the dark rate reduction at low temperatures.



Up to 6 orders of magnitude reduction in dark rate.  $\implies$  Excellent candidate for low count rate experiments!

The crosstalk can be derived from the ratio of dark rate with 0.5 and 1.5 p.e threshold. It is not temperature dependant.

# Summary ...

- SiPMs are appropriate detection devices for LAr scintillation light read out
- We know how they work at cryogenic temperatures. By cooling we can reduce the dark counts significantly without any loss of gain.

## ...and outlook

- Proof of principle experiment using SiPMs and WLS-fibre to read out LAr scintillation light has been accomplished. First results look very promising.
- Now we are building an improved setup.
- MC simulations for a GERDA like experiment with LAr veto will be done.

**Thank you for your attention**

# Correction curves

There is the problem of nonlinearity as more than one photon can hit the same pixel at once



→ However correction curves exist.

$$N_{fired} = N_{pix}(1 - e^{-N_{pe}/N_{pix}})(1 + p e^{-N_{pe}/N_{pix}})$$

$N_{pix}$  number of pixels

$p$  cross talk probability

$N_{pe} = N_{photons} \times Q.E.$



# Photon Detection Efficiency

- APD QE peak 70% is a typical value
- Fill factor is 78.5 , 61.5, 30.8 for the 100, 400, 1600 pixel MPPC's

