Poster OG2.5 / 2-P-107



28th International Cosmic Ray Conference Mirror alignment and performance of the optical system of the H.E.S.S. imaging atmospheric Cherenkov telescopes

R. Cornils^{1*}, S. Gillessen², I. Jung², W. Hofmann², and G. Heinzelmann¹, for the H.E.S.S. collaboration

¹Universität Hamburg, Institut für Experimentalphysik, Luruper Chaussee 149, D-22761 Hamburg, Germany ²Max-Planck-Institut für Kernphysik, PO Box 10 39 80, D-69029 Heidelberg, Germany *e-mail: René Cornils (cornils@mail.desy.de)



2003, Tsukuba, Japan



Abstract

H.E.S.S. is a stereoscopic system of large imaging atmospheric Cherenkov telescopes currently under construction in the Khomas Highland of Namibia with the first two telescopes already in operation. The reflector of each telescope consists of 380 mirror facets with 60 cm diameter and a total area of $107 \,\mathrm{m}^2$. The alignment of the mirror facets is performed by a fully automated alignment system using stars imaged onto the lid of the PMT camera. All mirror facets are mounted

onto supports which are equipped with two motor-driven actuators while optical feedback is provided by a CCD camera viewing the lid. The alignment procedure, implying the automatic analysis of CCD images and control of the mirror alignment actuators, has been proven to work reliably. On-axis, 80% of the reflected light is contained in a circle of less than 1 mrad diameter (1 mrad corresponds to 0.057° or 1.5 cm in the focal plane), well within specifications.

Mirror Alignment Technique

The mirror alignment is based on a fully automated scheme:

- Mirror supports with motor-driven actuators.
- Sophisticated control electronics.
- CCD camera for optical feedback.
- Completely computer controlled.

Major advantages of alignment technique:

- Natural point-like source at infinite distance.
- Direct imaging in the focal plane.
- Alignment of mirror facets at optimum elevation $(55^{\circ} - 75^{\circ})$.

Duration of mirror alignment:

- Initial alignment (only once): 2 weeks
- Realignment of all mirror facets (if required): 1–2 nights

Point Spread Function



width of psf	СТ03	CT02	CT04	specs
σ_{proj} [mrad]	0.23	0.23	0.23	\leq 0.50
σ_{2D} [mrad]	0.32	0.33	0.32	\leq 0.71
$r_{80\%}$ [mrad]	0.40	0.41	0.40	≤ 0.90
$r_{80\%}$ for individual mirrors				< 0.50

 σ_{proj} : rms of projected intensity distribution σ_{2D} : rms of two-dimensional distribution $r_{80\%}$: 80% containment radius

 \implies Very good average mirror quality. \implies Excellent alignment accuracy.

Dish Deformation

The alignment system provides a mechanism to study the deformation of the support structure in detail: Rather than combining all individual spots to a uniform main spot,



Mirror alignment technique: The telescope is pointed towards an appropriate star whereupon all mirror facets generate individual images of the alignment star in the focal plane (closed lid of the PMT camera). Actuator movements change the location of the corresponding image which is observed by a CCD camera.



Mirror facet with adjustable support:

- Mirror held by special joints to avoid stress.
- Two motor-driven actuators with two Hall sensors on each motor shaft for recording of movement.
- Resolution of actuator movement: $3.4 \,\mu\text{m}$ corresp. to 0.013 mrad. Range of adjustment: \pm 1.4 cm corresp. to \pm 52 mrad.



Light spots before and after the mirror alignment as seen by the CCD camera (log. scale).



On-axis intensity distribution of a star on the camera lid after alignment (CT04). The hexagonal border indicates the size of a pixel of the PMT Cherenkov camera. The complete amount of light is well within one pixel.









Point spread function with varying elevation. The curves are nearly flat in the usual working range ($45^{\circ}-90^{\circ}$), indicating a good stability of the support structure. In addition, all reflectors behave very similar.

CCD images of spot matrix at different elevations

 \rightarrow relative movement of spots \rightarrow deflection of mirror facets \rightarrow deformation of dish structure.

Left: Mirror deflections of CT03 at 29° eleva

the spots can be arranged in arbitrary patterns.

Spot matrix: Each spot corresponds to an individual mirror facet at a certain location in the dish (facets of CT03).

0.5 mra

tion with respect to 65° (mean alignment elevation), arrows scaled by the square root of the deflection.

Conclusion

The mirror alignment of the first three H.E.S.S. telescopes was a proof of concept and test of all technologies involved: mechanics, electronics, software, algorithms and the alignment technique itself. All components work as expected and the resulting point spread function significantly exceeds the specifications. The widening of the spot with increasing angle to the telescope axis is in accordance with the expected behaviour based on simulations and the variation of spot size with elevation is completely uncritical. All three reflectors behave very similar which demonstrates the high accuracy of the support structure and the reproducibility of the alignment process.

References

Bernlöhr, K. et al. 2003, The optical system of the H.E.S.S. imaging atmospheric Cherenkov telescopes, Part I: layout and components of the system, accepted for publication in Astropart. Phys.

Cornils, R. et al. 2003, The optical system of the H.E.S.S. imaging atmospheric Cherenkov telescopes, Part II: mirror alignment and point spread function, accepted for publication in Astropart. Phys.

Cornils, R. & Jung, I. 2001, Proceedings of The 27th International Cosmic Ray Conference, eds. M. Simon, E. Lorenz, & M. Pohl (Copernicus Gesellschaft), vol. 7, p. 2879-2882

Cornils, R. et al. 2003, The Universe Viewed in Gamma-Rays, eds. R. Enomoto, M. Mori, & S. Yanagita (Universal Academy Press), p. 403-408