



MAX-PLANCK-GESELLSCHAFT

# Operation of a GERDA phase I prototype detector in liquid argon and nitrogen



Marik Barnabé Heider, Max-Planck für Kernphysik

March 2007, DPG, Heidelberg

# Outline

- GERDA phase I
- Enriched detectors
- Testing with prototype diode
- Lowmass Cu holder
- GERDA Detector Laboratory
- Summary of 1 year measurement with Phase I detector prototype

# GERmaniumDetector Array for the search of neutrinoless $\beta\beta$ decays of $^{76}\text{Ge}$

- PHASE I

- Enriched  $^{76}\text{Ge}$  (86%)
  - HEIDELBERG-MOSCOW (5) and IGEX (3) detectors  $\rightarrow$  17.9 kg
- Nonenriched Ge
  - Genius detectors (6)  $\rightarrow$  15 kg
- 1 year data taking
- Bkg = 0.01 cts/keV/kg/year



GERDA PHASE I detectors mounted vertically into strings in low-mass Cu support operated in LAr/LN<sub>2</sub>

# Enriched diodes

- In GERDA Detector Laboratory, LNGS ...



Energy resolution measured in their cryostats



Opening and dimensions measurement



Keep under vacuum in transportation container



Refurbishment at Carberra Semiconductor, Olen, Belgium

March 2007, DPG, Heidelberg

# GERDA phase I prototype diode

- Non-enriched HP p-type Ge diode to test
  - GERDA phase I low mass support
  - Cooling/warming cycles
  - Test bench facility of the GERDA Detector Lab
  - Detector stability in LAr/LN<sub>2</sub>
  - Refurbishment procedure


➔ To be ready for the enriched diodes



Prototype diode (total mass 1.6 kg) refurbished by CANBERRA using the same technology as for the enriched diodes. The FWHM in a test cryostat is 2.2 keV at 1.332 MeV.



# GERDA phase I detector assembly

- Lowmass Cu holder
  - Lowactivity Cu (80 g)
  - PTFE
  - Silicon



# GERDA phase I detector assembly

- Testing at Canberra
  - Mounting procedure
  - Signal and central HV contact quality
  - Mechanical stability
  - Spectroscopy performance



Same resolution as obtained  
in a test cryostat!

March 2007, DPG, Heidelberg


# GERDA Detector underground Laboratory, LNGS



Detector test bench, Rn 'free bench' and clean bench. Ar level is monitored by weighting cells, Rn by Lucas cell (10 Bq/m<sup>3</sup>) and humidity is kept low (30%).

- To test the enriched detectors


- Clean room level 10 000
- Clean bench and Rn 'free bench' level 10



March 2007, DPG, Heidelberg


# Detector test bench

- Infrared shield
- WarmFET
- 1 mcables
- LAr: 1 filling/week



# Detector 'health' monitoring


- Signal to HV resistivity measurement




- Test point, picoammeter and noise level recorded



- Forward resistivity measurement while cooling





- Spectra collecting



# Detector 'health' monitoring

- Leakage current probe
  - I-V curve of diodes



March 2007, DPG, Heidelberg

# GERDA phase I prototype diode ...

## 1 year testing

- LN<sub>2</sub> and LAr
- 43 cooling-warming cycles
  - To performed detector mounting and/or electronics modifications
- 2 refurbishments
  - New passivation layer evaporated
  - Total exposure to cosmic rays ~ 60 hours
- Detector parameters stable over long term measurement
  - 2 months
  - Physics results: Limit on the radiative 0v ECEC decay of <sup>36</sup>Ar, O.Chkvorets
- Spectroscopy performance: 3.4 keV FWHM at 1.332 MeV

## Enriched detectors status

- Refurbishment procedure is on going
  - ANG 1 and RG 3 are refurbished and ready to be tested in GDL
  - ANG 2-5, RG 1-2, Genius 1-6 are being refurbished at Canberra Semiconductor, Olen, Belgium

# Conclusion

- Gerda Detector underground Laboratory, LNGS, is operated for GERDA phase 1
- Enriched detectors are being refurbishment
- 1 year testing with prototype detector
  - Lowmass holder
  - Cooling/warming cycles
  - Operation in LAr and LN<sub>2</sub>
  - Refurbishment procedure
  - Long term measurement