

# Current status of prototype detector testing


---

M.Barnabé Heider, O.Chkvorets, K.Gusev, S.Schör

# New design of the dewar


---

- Copper cylinder
  - Infra-red shielding
- Filling from top
  - Prevent violent filling
  - 1 filling / week



# Mounting of the dewar

---



Mounting of the copper cylinder



Suspension system

# LAr weighing system


- Temperature sensors removed
- 3 weighing cells installed
  - Precision of 200 g (~0.1 cm height)
  - Evaporation rate : 2 cm/day → 4.5 kg/day



# Mounting in 'Rn-free' clean bench

---

Clean room level



---

November 14, 2006

Marik Barnabé Heider, GERDA meeting, Milano

# ''Rn-free'' test bench

## □ Radon concentration

□ Reduced by applying a N<sub>2</sub> flux

□ C<sub>Rn</sub> monitored with a 7 L Lucas cell

■ C<sub>Rn</sub> ~ 2 Bq/m<sup>3</sup> with high N<sub>2</sub> flux

■ C<sub>Rn</sub> ~ 4 Bq/m<sup>3</sup> with N<sub>2</sub> flux of 1 L/min


□ Plan

■ Higher N<sub>2</sub> flux

■ Use of electro-static chamber for monitoring C<sub>Rn</sub> < 1 Bq/m<sup>3</sup>



Lucas cell and electronics




# Test with prototype diode

---

- In the "Rn-free" detector test bench
  - Mounting
  - Signal to high voltage resistivity measurement
  - Forward resistivity measurement
  - I-V curve measurement
    - Infra-red shielding efficient
    - 4<sup>th</sup> cooling cycle → Increasing of current at


# I-V curve



# Spectroscopy measurement

---

Date	HV (Volt)	FWHM (keV)	Shaping time ( $\mu$ s)	Cable length (cm)
September 06	4000	4.5	13	80
November 06	4000	4.1	3	100

Resolution at 1.332 MeV  
with 1 m signal cable  4.1 keV

# Summary

---

- Improved test bench dewar installed
  - Infra-red shielding
  - Filling from the top
  - LAr weighing system
- Full prototype testing in "Rn-free" clean bench performed
  - Mounting and measurement with gloves feasible
  - Energy resolution obtained : 4.1 keV (1 m cable and warm FET)
- Set up ready for testing of enriched detectors